

FISH ZIRCON TECHNICAL DATASHEET

FZ18 ZIRCON FISH CABINET



FZ18

Dimensions (mm)	External	Internal
Width	595	445
Depth	722	598
Height	1906	1250
Door Opening		1276
Capacity		
Capacity (kg)		114

KEY FEATURES

- Foodsafe stainless steel exterior and interior
- CoolSmart controller
- Designed and engineered to operate efficiently up to a 43°C ambient
- Self closing doors
- Precision injected, high density 75mm polyurethane insulation
- Cabinet designed and fitted with low level heavy-duty, non-marking swivel castors with brakes to front
- Barrel locked doors
- 7 polypropylene containers, each with a removable slime tray
- Drained through the base into unit compartment exiting to rear - drain should be connected to a permanent waste or suitable container

OPTIONS

- Bottom mounted refrigeration system
- Connection to third party supervisory communication systems such as BMS is possible using proprietary equipment. Please contact Williams for more information.
- 25mm adjustable levelling feet



FISH ZIRCON TECHNICAL DATA

Fish Zircon	FZ18
Temperature (°C)	-2/+2
Power Supply	220V/240V 50Hz/1Ph
Fuse (Amps)	13
Defrost	Manual
Noise Level (dBA)	50.0
Fittings	
Shelves	7 polypropylene trays
Electrical Data - Standard Refrigerant	
Refrigerant	R290
Energy Consumption (kW / 24hrs)*	2.05
Start Up (Amps)	6.6
Running (Amps)	1
Heat Rejection (kW / 24hrs)**	692

IMPORTANT NOTES:

*Energy consumption is tested to EN153 in 24hrs

**Heat rejection is evaporating at -10°C in 32°C Ambient

All refrigeration equipment requires adequate ventilation for efficient and effective performance.

Williams is committed to a policy of continual product development and innovation. As such, we reserve the right to change product specifications stated without prior notice.

Williams Refrigeration
Bryggen Road,
North Lynn Industrial Estate
King's Lynn, Norfolk. PE30 2HZ

T +44(0) 1553 817 000
Spares: +44(0) 1553 817 017
E info@williams-refrigeration.co.uk
W www.williams-refrigeration.co.uk

